




# LaYZr™ Tungsten

Gas Saver Kit

Flex-Loc™ Torch



New LaYZr™ (1.5% Lanthanum, 0.08% Yttrium, 0.08% Zirconium) Tungsten, (color-coded Chartreuse) is non-radioactive and has great properties that make it best at automated or robotic applications. LaYZr™ can be run in Alternating or Direct Current using inverter or transformer based constant current power sources. It has a very stable tip geometry and runs 30% cooler than 2% Thoriated, with longer life.

Size		Part Number	
Inches	Millimeters	10-Pack	3-Pack
.020 x 7"	0.5 x 175mm	T0207GTM	
.040 x 7"	1.0 x 175mm	T0407GTM	
1/16 x 7"	1.6 x 175mm	T1167GTM	T1167GTM-3
3/32 x 7"	2.4 x 175mm	T3327GTM	T3327GTM-3
1/8 x 7"	3.2 x 175mm	T187GTM	T187GTM-3
5/32 x 7"	4.0 x 175mm	T5327GTM	

CK Worldwide, Inc  
P.O. Box 1636, Auburn, WA 98071 USA  
Phone: 1.800.426.0877  
Fax: 1.800.327.5038

Form 452  
www.CKWORLDWIDE.com

Connect with us on:



# The Flex-Loc™



- 360 degree variable angle torch head
- Locks in any position
- Interchangeable head allows different configurations and head sizes
- Great for "walking the cup" on open root welds for pipe welding
- Access hard to reach welds ergonomically


## Gas Cooled

### FL130 & FL130V (130amps)

Head Style	Cable	Cable Length	Standard #	Superflex #
FL2L	1 Piece	12 1/2 ft.	FL1312	FL1312SF
		25 ft.	FL1325	FL1325SF
FL2L w/ valve	1 Piece	12 1/2 ft.	FL1312V	FL1312VSF
		25 ft.	FL1325V	FL1325VSF

### FL150 & FL150V (150amps)

Head Style	Cable	Cable Length	Standard #	Superflex #
FL3L	1 Piece	12 1/2 ft.	FL1512	FL1512SF
		25 ft.	FL1525	FL1525SF
FL3L w/ valve	1 Piece	12 1/2 ft.	FL1512V	FL1512VSF
		25 ft.	FL1525V	FL1525VSF



Example of the FL150 with Valve option.

*(Not available on Water Cooled)*

## Water Cooled

### FL230 (230amps) & FL250 (250amps)

Head Style	Cable	Cable Length	Standard #	Superflex #
FL2L	TriFlex or Superflex	12 1/2 ft.	FL2312	FL2312SF
		25 ft.	FL2325	FL2325SF
FL3L	TriFlex or Superflex	12 1/2 ft.	FL2512	FL2512SF
		25 ft.	FL2525	FL2525SF